

13/1/06

15

6 SL 26.476
25 4508
26 07 21 26.096
28 41 00 33.040

72 35 52 497
26.44
343 22 18 17.657
318 39 11 47.738

No. Fail B207F

Rajah di muka

Stesen	BEARING / SUDUT			Dari Stn.	GARISAN		Ke Stn.	Sudut Pugak (±)	Jarak	Suhu	Jarak Antara Tupang	Jarak Mukamat
	Penyilang Kiri	Penyilang Kanan	Purata		Bearing Mukamat							
	Beng anduran		100 15 20	2	100 23 50		1	H				56.518
			mt 08 30		Pk.B							
			100 23 50									
1	100 5 20	280 15 20	87 16 20	2	87 24 50		3	H				58.006
2			mt 08 30		Pk.B							
3	87 16 20	267 16 20										
			87 24 50									
1	Seperti di atas		107 34 10	2	107 42 40		4	H				23.136
2			mt 08 30		Pk.B							
4	107 34 10	287 34 10										
			107 42 40									
1	Seperti di atas		343 12 10	2	343 20 40		5	H				17.008
2			mt 08 30		Pk.B							
5	343 12 10	163 12 10										
			343 20 40									
1	Seperti di atas		284 56 20	2	285 04 50		6	H				30.183
2			mt 08 30		Pk.B							
6	284 56 20	104 56 20										
			285 04 47									
2	104 56 20	284 56 20	25 46 20	6	25 54 40		7	H				44.575
6			mt 08 30		Pk.B							
7	25 46 20	205 46 20										
			25 54 44									
6	205 46 50	25 46 50	25 49 20	7	25 57 40		8	H				25.988
7			mt 08 24		Pk.B							
8	25 49 20	205 49 20										
			25 57 44									

286 31 39 20.318 8-4 165 18 49 80.945 286 37 35 21 289 05 05 4.988
289 23 35 4.994 165 27 18 80.937 (m) 98 13 57 11.52 122 24 33 7.354
291 33 09 4.146 104 204 16 46 84.148 204 24 11 84.111 (m) 98 40 30 20.345 173 19 26 25.189
94 42 15 12.083 - 9 25 13.4 209 01 03 64.943 174 59 09 28.137
97 09 02 28.164 209 07 38 64.938 (m)

No. Fail

- 06 35 40.005

Rajah di muka

Stesen	BEARING / SUDUT			Dari Stn.	GARISAN		Ke Stn.	Sudut Pugak (±)	Jarak	Suhu	Jarak Antara Tupang	Jarak Mukamat
	Penyilang Kiri	Penyilang Kanan	Purata		Bearing Mukamat							
6	205 46 50	25 46 50	32 49 40	7	32 58 00		9	H				34.560
7			mt 08 30		Pk.B							
9	32 49 40	212 49 40										
			32 58 01									
7	212 49 40	32 49 40	98 38 10	9	98 46 30		10	H				48.254
9			mt 08 24		Pk.B							
10	98 38 10	278 38 10										
			98 46 31									
7	Seperti di atas		151 56 40	9	152 05 00		11	H				39.737
9			mt 08 30		Pk.B							
11	151 56 40	331 56 40										
			152 04 59									
9	331 56 40	151 56 40	72 06 00	11	72 14 20		12	H				32.735
11			mt 08 30		Pk.B							
12	72 06 00	252 06 00										
			72 14 16									
11	252 06 00	72 06 00	247 37 40	12	247 46 00		13	H				5.658
12			mt 08 16		Pk.B							
13	247 37 40	67 37 40										
			247 45 56									
11	Seperti di atas		182 55 45	12	183 04 00		1	H				62.102
12			mt 08 30		Pk.B							
1	182 55 45	2 55 45										
			183 03 58									
12	2 55 45	182 55 45	280 15 40	1	280 23 50		2	H				56.520
1			mt 08 30		Pk.B							
2	280 15 40	180 15 40										
			280 23 50									

Garis 1-2 dibaca

Seperti

Tikuan

Pembetulan

280 15 40

280 15 20

20 per 7 sen

02.86 per sen

45

11

28

No. Fail

Rajah di muka

Stesen	BEARING / SUDUT		Dari Stn.	GARISAN	Ke Stn.	Sudut Pukak (±)	Jarak	Suhu	Jarak Antara Tupang	Jarak Mukamat
	Penyilang Kiri	Penyilang Kanan		Bearing Mukamat						
12	182 55 00	2 58 00								
1										
14										
2	280 15 20	100 15 20	302 33 10	302 41 40	14	H				30-410
1			14 08 30		Pk.B					
14	302 33 10	122 33 10								
1	302 41 40									
14										
15	97 08 00		28 165	Pk.L	(Tanam Vegetasi)					
16	94 40 00		12 083	Pk.B						
17	291 39 40		4 148	Pk.B						
18	289 05 10		4 988	Pk.L	Pp.B					
19	286 33 00		20 319	Pk.B						
6	205 54 40	25 54 40								
7										
20	91 42 30		8 551	Pk.L						
7	212 58 00	32 58 00								
9										
21	280 37 30		5 221	Pk.B						
22	98 14 00		11 521	Pk.B						
23	98 40 30		24 345	Pk.B						
24										

No. Fail

Rajah di muka

Stesen	BEARING / SUDUT		Dari Stn.	GARISAN	Ke Stn.	Sudut Pukak (±)	Jarak	Suhu	Jarak Antara Tupang	Jarak Mukamat
	Penyilang Kiri	Penyilang Kanan		Bearing Mukamat						
11	252 14 20	72 14 20								
12										
24	289 28 40		4 961	Pk.B						
25	250 46 20	7 028								
12	72 14 20	252 14 20								
11										
24	66 17 10		28 942	Pk.B						
25	80 47 10		37 929	Pk.B						
26	87 52 40		36 623	Pk.B						
27	113 49 30		37 176	Pk.B						
28	118 15 50		38 071	Pk.B						
29	77 46 47 00		20 368	Pk.B						
30	72 37 56		25 710	Pk.B						
31	58 36 20		11 375	Pk.B						
32	53 14 30		12 417	Pk.B						
33	35 42 40		9 958	Pk.B						
34	332 31 20		11 063	Pk.B						
35	325 55 40		9 631	Pk.B						
36	308 40 20		14 212	Pk.B						
37	289 39 20		6 700	Pk.B						
38	259 00 50		13 137	Pk.B						
39	244 43 20		7 960	Pk.B						
40	235 02 20		9 157	Pk.B						
41	158 25 30		7 367	Pk.B						
42	135 12 40		10 737	Pk.B						
43	128 05 10		9 913	Pk.B						
44	112 39 00		20 420	Pk.B						
45	110 19 50		24 529	Pk.B						

Enclosure Lot 43350

11-85 56 50 52 689 7
 11-80 30 20 37 469 } Edge of
 48 113 52 00 37 109 } Concrete wall
 48 111 49 00 43 218 } Thickness = 0.25

