

Client

Sying Kong

Date

JM 2057

Location

Purpose

50

From	To	RL of Station	Inst. Ht.	Bearing	Vertical Angle + or -	Lower Wire	Middle Wire	Upper Wire	Gen. No.	Horiz. Dist.	Ht. Diff. + or -	RL of Inst.	RL of Centre Reading	m	RL Object	Remarks
1.020 (1.335)							5.286			78m F2720			1.52701			
1.951 (1.976)			1.902 (1.900)				9.909									
1.595 (1.507)			1.976 (1.989)				9.879									
1.631 (1.535)			1.513 (1.996)			9.911	9.820									
5.687 -			1.025 (1.336)				5.517 -			78m F2221 / 78m 3 / F220						RL: 5.517
			5.916 -													
1.025 (1.336)							5.517			78m F2222						
1.375 (1.951) 1.951			1.957 (1.978)				5.085			F1001						
1.951 (1.976)			1.595 (1.523)				9.865									
			1.252 (1.910)				5.069			F21						
1.970 (1.982)			1.610 (1.529)				9.706			F1003						
1.399 (1.943)			1.971 (1.983)				9.705									
			1.580 (1.519)				9.979			F1112						
1.196 (1.376)			1.272 (1.917)				9.782			F22						
1.591 (1.506)			1.998 (1.991)				9.930									
1.367 (1.998)			1.529 (1.500)				9.997			F1191						
			1.315 (1.931)				9.999			78m F2222 / F223						
1.526 (1.504)			1.391 (1.956)				9.923									
2.328 (1.769)			1.992 (1.990)				9.957									
			1.505 (1.999)				5.280									
			0.517 (1.091)				6.208 -			F1007						
14.578 -			13.887 -							78m F2223 / F226						