

1st floor (G).

No. Fail W0059 Capital Square Retail

Rajah di muka

[illegible]

Rajah di muka

Stesen	BEARING / SUDUT			Dari Stn.	GARISAN		Ke Stn.	Sudut Pukak (°)	Jarak	Suhu	Jarak Antara Tupang	Jarak Mukamat
	Penyilang Kiri	Penyilang Kanan	Purata		Bearing Mukamat							
109	232 91 55	52 91 55	333 11 53	105	333 12 00	106	4	27.609				27.609
105			4 7					27.609				
106	333 11 53	153 11 53										
	p.t.B											
105	153 11 53	333 11 53	30 49 98	106	30 49 57	107	4	81.710				81.710
106			4 9					81.710				
107	30 49 98	210 49 98										
	p.t.B											
GL 108	162 06 39	162 06 39	M1 9	108	162 06 98	109	4	2.068	GL			
GL 106/109	32 09 55	212 09 55	M1 9	106	212 05 09	109	4	11.929	GL			
GL 110	50 19 15	290 19 15	M1 9	106	290 19 29	110	4	13.915	GL			
GL 111	30 39 29	210 39 29	M1 9	106	210 39 38	111	4	35.519	GL			
106	210 49 98	30 49 98	139 18 36	107	139 18 46	112	4	73.339				73.339
107			4 10					73.338				
GL 112	139 18 46	319 18 36										
	p.t.L (GL)											
GL 113	118 43 11	298 43 11	M1 10	107	298 43 21	113	4	16.087	GL			16.087
GL 107/119	119 10 07	359 10 07	M1 10	107	359 10 17	119	4	31.548	GL			
GL 115	222 23 16	202 23 16	M1 10	107	202 23 26	115	4	7.518	GL			
GL 116	27 36 09	207 36 09	M1 10	107	207 36 19	116	4	25.111	GL			
GL 117	28 49 36	208 49 36	M1 10	107	208 49 46	117	4	53.969	GL			
107	319 18 36	139 18 36	92 09 38	112	92 09 50	118	4	45.589				45.589
112			4 10					45.586				
GL 118	92 09 38	222 09 38										
	p.t.L (GL)											

No. Fail _____

Rajah di muka

[illegible]

4

Rajah di muka

[illegible]

No. Fail

274 f/kan

Rajah di muka

Stesen	BEARING / SUDUT			Dari Stn.	GARISAN		Ke Stn.	Sudut Pagak (±)	Jarak	Suhu	Jarak Antara Tupang	Jarak Mukamat
	Penyilang Kiri	Penyilang Kanan	Purata		Bearing Mukamat							
103	81 51 19	261 51 19	59 08 05	109	59 08 08	205	H	62.208				62.208
109			M, 1 9					89 11	62.202			
205	59 08 05	239 08 05	c 1					95 46				
	pk.B											
109	239 08 05	59 08 05	95 19 35	205	95 19 36	206	H	41.769				41.769
205			M, 1 9					41.768				
206	95 19 35	225 19 35	c 3									
	pk.L (V113)											
205	225 19 35	95 19 35	29 48 15	206	29 48 15	207	H	60.789				60.789
206			M, 1 9					60.782				
207	29 48 15	209 48 15	c 9									
	pk.L (V105)											
206	209 48 15	29 48 15		207		208	H	69.685				69.685
207												
208	36 19 25											
206	209 48 15	29 48 15	90 05 53	207	90 05 52	208	H	58.910				58.910
207			M, 1 9					58.910				
208	90 05 53	220 05 53	c 5									
	pk.B											
207	220 05 53	90 05 53	58 29 45	208	58 29 42	201	95.53	41.258				
208			M, 1 9									
101	58 29 45	238 29 45	c 7									
	pk.											
208	238 29 45	58 29 45	8 01 20	101	8 01 16	412	Sila Rujuk m/s 1 R3					
101			M, 1 9		Bering							
412	8 01 20	188 01 20	c 8		Tutup.							

Rajah di muka

[illegible]

W² F/007

Rajah di muka

[illegible]

Rajah di muka

[illegible]

Rajah di muka

[illegible]

No. Fail

Rajah di muka

Stesen	BEARING / SUDUT			Dari Stn.	GARISAN		Ke Stn.	Sudut Pugak ($\pm$)	Jarak	Suhu	Jarak Antara Tupang	Jarak Muktamad
	Penyilang Kiri	Penyilang Kanan	Purata		Bearing Muktamad							
710	255 75 70	55 75 50	10 00 70	101	8 01 16	1/2	57/4	Rujuk m/s 1	1.3			
101	0	188	m. 7		Bering							
1/2	10 00 70	198 00 70	01 32		Tertutup.							
	Bering 101 - 1/2 Aibaca				8 00 79							
	Sepatutnya Aibaca				188 01 16							
	Titik				- 32' uk 8 sh							
	Pembetulan.				+ 9"							
									</			

