

Rajah di muka

[illegible]

[illegible]

Rajah di muka

[illegible]

[illegible]

No. Fail

Rajah di muka

Stesen	BEARING / SUDUT			Dari Stn.	GARISAN		Ke Stn.	Sudut Pukak (±)	Jarak	Suhu	Jarak Antara Tupang	Jarak Muktamat
	Penyilang Kiri	Penyilang Kanan	Purata		Bearing Muktamat							
56	102 09 11	282 09 11	289 56 00	57	289 57 08	61	90 92	21.89				21.89
57			MT 1 08				(mini)					
61	289 56 00	109 56 00										
	Sp.L (B501)											
56	S. D. A.	289 22 15	57	289 23 20	62	88 19	27.25					27.25
57		MT 1 08					(mini)					
62	289 22 15	109 22 15										
	Pt.L (B502)											
56	S. D. A.	293 20 39	57	293 21 48	63	85 11	45.912					45.912
57		MT 1 08					(mini)					
63	293 20 39	113 20 39										
	Sp.L (B503)											
56	S. D. A.	299 58 02	57	299 59 17	67	87 30	41.09					41.09
57		ct 1 15					41.09					
67	299 58 02	117 58 02										
	Pt.L											
57	117 58 02	299 58 02	80 47 17	69	280 48 39	65	98 52	17.79				17.79
69			ct 1 22				17.79					
65	280 47 17	80 47 17										
	Pt.L (old sta F30)											
69	80 47 17	280 47 17	22 37 45	65	282 39 19	66	91 02	109.88				
65			ct 1 29									
66	282 37 45	22 37 45										
	Pt.L (old sta F30)											
Bearing 65-66 dibaca 282 37 45												
Sepatutnya dibaca 22 37 19												
Tikisan - 1 29' utk 13 sta.												
Pembetulan, + 7" per sta												
282 37 23 0.009												
C: 0.003 0.009												
C: 1: 99,842												

[illegible]

